

Product Name :
Portable Non-Contact Ink Jet Pen

Product Code :
EQUP-MC20087-0009

Description :

Portable Non-Contact Ink Jet Pen

Technical Specification :

Automation Grade Semi-Automatic
Color & Page Single Color
USB Available Yes
Is It CE Certified Ce Certified

Portable Non-Contact Ink Jet Pen which is a Zero Maintenance, 300 dpi high resolution, Battery Powered ONE line (character height 3.2 mm) Printer & can be used on any Porous products to print etc. on labels, cartons, etc. It is fully programmable through the computer where it can print 1 line of Data at a very low price. This printer is a totally mobile Solution for Time Date Numbering,...uses such as; Parts Marking, Package Marking and validating in surgeries, pharmacies, and hospitals, marking dockets and packages in transit, quality control validation, laboratory timing and checking, production controls, delicate product marking, nightclub and meetings entry validation, etc.

Languages	English, Spanish, French, German, etc.
Input Device	USB Interface with Computer
Printing Area	1 line of 3.2 mm with max. 40 characters.
Message Capacity	Stores 1 message at 1 time.
Prints Using	TIJ 2.5 Print-head for spraying ink
Print Distance	Max. 6 mm from substrate down or in front.
Inking Medium	4 cc disposable pre-mix ink in Cartridge form with head.
Printing Medium	Solvent/Oil based inks (black, red*, magenta*, etc.)
Ink Drying Time	Min. 5 seconds on plastics & laminates.
Impressions	Appx. 1 Million char. of 2 mm per cartridge of ink.
Operating Range	10 ~ +55°C 10% - 85% RH, non-condensing.
Supply Voltage	1Ø 90 - 240 Vac, 50/60 Hz, 5 W
Dimensions	L173 x W32 x H43 mm

Weight	125 g excluding cartridge & battery.
--------	--------------------------------------

a. 2 Nos. AA Rechargeable Batteries, Computer Software, USB Data Transfer Cable.

b. 1 No. disposable Pre-mix Black ink cartridge, Cartridge cleaning Wipe.

c. Operator Tool Kit, Operation & User Manual, Configuration Software on CD



Equip Machines China

Email us at: sales@equipmentsmachines.com